

Mobilgrease XHP™ 462 saves Mukand Steel US\$46,287 annually with 6 times longer regreasing interval



Energy lives here

Danieli Morgårdshammar WRM Stand

Steel Manufacturer | Thane, India

SITUATION

Mukand Steel had been using a third-party NLGI 2 grease for lubrication of its WRM stand bearings. This resulted in short re-greasing intervals of 12 hours due to water wash-off and poor cohesion of the grease.

BENEFIT



Safety Hour exposure reduction 2,970 Hours



Environmental Care*

Environmental improvement 18,017 kg



Productivity

Revenue improvement L

US\$46,287

RECOMMENDATION

After studying the issue, the ExxonMobil technical team recommended the use of **Mobilgrease XHP™ 462**. An extended service lithium complex grease, it offers excellent adhesion, structural stability, and resistance to water contamination.

IMPACT

The superior performance of **Mobilgrease XHP 462** has helped extend the re-greasing interval by 6 times, from 12 hours to 72 hours, along with increased bearing protection. This has led to a reduction in operating costs and improvement in equipment reliability for an annual saving of US\$46,287.

Industrial Lubricants



Advancing Productivity

Helping you reach your Safety, Environmental Care and Productivity goals through our innovative lubricants and services is our highest priority. That's Advancing Productivity. And that's how we help you achieve your broader vision of success.

This Proof of Performance is based on the experience of a single customer. Actual results can vary depending upon the type of equipment used and its maintenance, operating conditions and environment, and any prior lubricant used. For more information on other Mobil* –branded industrial lubricants and services, contact your local ExxonMobil representative. Images featured may not be representative of actual site conditions or environment. *Visit mobil.com/industrial to learn how certain Mobil-branded lubricants may provide benefits to help reduce environmental impact. Actual benefits will depend upon product selected, operating conditions and applications.

© 2018 Exxon Mobil Corporation. All rights reserved. All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its affiliates unless otherwise noted.