Easy noise level measurement

SKF Sound Pressure Meter TMSP 1

The SKF TMSP 1 is a high quality, handheld instrument for measuring the sound level in decibels. The environmental noise is picked up by the microphone and then processed by the handset. The noise can be monitored both quantitatively and qualitatively. The SKF Sound Pressure Meter is supplied in a carrying case complete with windshield, calibration screwdriver, jack for external outputs and an alkaline battery.

- User friendly and easy to operate, no special training required.
- dBA and dBC scale weightings for both general sound level and low frequency noise measurements.
- Fast and slow time weighting enables either normal measurements or the average level of fluctuating noise.
- Four different measurement scales to suit almost all situations.
- User selectable backlight for use in environments with poor lighting.
- Four digit LCD panel with both digital and bar graph display.
- Max and min function for peak measurements and alarm function to indicate when the noise level is too low or too high.
- Tripod mounting thread for use when the instrument must remain in the same position for a prolonged period.









_					٠			٠			
т	Δ	~	h	n	п	•	31	4	2	٠	2

Designation	TMSP 1				
Frequency range	31,5 Hz to 8 kHz				
Measuring level range	30 to 130 dB				
Display	LCD				
Digital display	4 digits, Resolution: 0,1 dB, Display update: 0,5 s				
Analogue display	50 segments bar-graph Resolution: 1 dB Display update: 100 ms				
Time weighting	Fast (125 ms), Slow (1 s)				
Level ranges	Lo = 30~80 dB, Med = 50~100 dB, Hi = 80~130 dB, Auto = 30~130 dB				
Accuracy	±1,5 dB (ref 94 dB at 1 kHz)				
Conformity	Fulfills IEC651 type 2, ANSI S1.4 type 2 for sound level meters				

Dynamic range	50 dB				
Power supply	9 V Alkaline type IEC 6LR61				
Power life	50 hours (with alkaline battery)				
Operation temperature	0 to 40 °C (32 to 104 °F)				
Operation humidity	10 to 90% relative humidity				
Operation altitude	Up to 2 000 m (6 560 ft) above sea level				
Dimensions	$275 \times 64 \times 30 \text{ mm} (10.8 \times 2.5 \times 1.2 \text{ in.})$				
Case dimensions	$530 \times 85 \times 180 \text{ mm} (20.9 \times 3.4 \times 7.0 \text{ in.})$				
Weight	285 g (0.76 lb) including battery				
Total weight (incl.case)	1 190 g (2.6 lb)				

 $\ensuremath{\mathbb{R}}$ SKF is a registered trademark of the SKF Group.

© SKF Group 2014

The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.



